

BID FORM PRICE SHEET

Addendum 1

Item #	Equipment Type	Make	Model	Qty	Unit Price	Shipping Per Unit	Delivery Time	Wty
1	<p>Kettle Mixer, Cook Cleveland Range Model No. HAMKDL200TCC HA-Series (HAMKDL) 200 Gallon (757 Liter) Direct Steam Mixer Kettles, Power Tilt, HA-Series, Horizontal Agitator, Variable Speed Control, 3 HP Agitator Drive, 3" Air Piston Valve, Built In Two Piece Spring Assist Cover With Built In Safety Screen, 70 Psi Steam Jacket Rating, 316 Stainless Steel Liner Standard, DPK Double Pantry Faucet, Gallon Markings On Inside Kettle Jacket (10 Gallon/40 Liters Increments) 208v/60/3-ph, 25.0 amps, standard FPVA3 3" Air Operated Flush Piston Valve (requires air compressor) GMC1/LMC1 Automatic Water Meter (gallons), build into console mounted (specify gallons or liters), used with 3/4" filler hose NOTE: Replaces Hot & Cold Water Faucet HA-TCR-DTCI Temperature chart recorder with digital temperature control & indicator (console mounted) HA-FS-200 Half-Moon Food Strainer, for tilting 200 gallon horizontal agitator mixer kettle Class 85 Weight: 1325 lbs total</p>	Cleveland	HAMKDL200TCC	1				
2	<p>Kettle Mixer, Direct-Steam Cleveland Range Model No. MKDL100T Kettle/Mixer, direct, sweep/fold agitator, 100-gallon capacity, 2/3 steam jacket design, 316 series stainless steel liner, tilt-type, variable speed control, two-piece cover with screen, H/C faucet, 3" butterfly draw-off, open leg base, stainless steel construction Dimensions 57.75(h) x</p>	Cleveland	MKDL100T	1				

	69.5(w) x 43.75(d) FS100 Half Moon Strainer, 100 gallons 208/240v/60/3-ph, standard FPVA3 3" Air Operated Flush Piston Valve (requires air compressor) GMC1/LMC1 Automatic Water Meter (gallons), build into console mounted (specify gallons or liters), used with 3/4" filler hose TCR-DTCI Temperature chart recorder with digital temperature control & indicator (console mounted) Class 85 Weight: 910 lbs total							
3	Cook Chill Filling Station Cleveland Range Model No. MFS Product Metering Filling Station, narrow design, only 21" wide, air operated piston pump with adjustable stroke from 20 to 128oz., easily disassembled for cleaning, speed controls in both directions, safety switch. SZ4135L Air Operated Casing Clipper, left hand, automatic clip feeding mechanism, safety shut-off valve, air pressure gauge, UTILITIES: air supply: 80 psi / 9 CFM Approximately	Cleveland	MFS	1				
4	Steamer, Pressure, Direct Steam Cleveland Range Model No. PDL3 Pressure Steamer, direct steam, 3-compartments, (8) 12" x 20" x 2-1/2" deep pan capacity each, individual automatic timers, designed for 5 psi direct steam, pressure regulating valve, cast aluminum doors, stainless steel frame, (4) 6" adjustable legs with flanged feet, 115v/60/1-ph Dimensions 61.63(h) x 39(w) x 39.5(d) NOTE: Clean, non toxic, uncontaminated steam is required for all "Direct Steam" steamers	Cleveland	PDL3	2				
Installation		Hourly Rate for Installation						